EVW1S7P02

EVlink Parking - wall mounted - 7 kW - 1xT2 - charging station





Main

TVI CALL	
Range	EVlink
Product name	EVlink parking
Product or component type	Charging station
Poles description	1P + N for power circuit 1P + N for control circuit
Mounting mode	Wall-mounted
Offer type	Standard
Max power	7 kW
Socket-outlet number	1
Socket-outlet type	T2 right

Complementary

230 V AC 50/60 Hz power circuit	
230 V AC 50/60 Hz control circuit	
TN	
Π	
32 A	
1 red push-button function : stop	
1 green illuminated push-button function : unlock flap	
1 red LED function : not operational	
1 orange LED function : reserved	
1 green LED function : available	
1 green LED flashing function : on charge	
460 mm	
330 mm	
165 mm	
25.7 kg	
IEC 61851-1	
IEC 61851-22	
CE	
СВ	
	230 V AC 50/60 Hz control circuit TN TT 32 A 1 red push-button function : stop 1 green illuminated push-button function : unlock flap 1 red LED function : not operational 1 orange LED function : reserved 1 green LED function : available 1 green LED flashing function : on charge 460 mm 330 mm 165 mm 25.7 kg IEC 61851-1 IEC 61851-22 CE

Environment

IP degree of protection	IP54 on load IEC 61851-1 IP54 off load IEC 61851-1	
IK degree of protection	IK08 socket-outlet IEC 61851-22 IK10 charging station IEC 61851-22	-
Ambient air temperature for operation	-2550 °C conforming to IEC 61851-22	
Ambient air temperature for storage	-4080 °C	
Operating altitude	02000 m conforming to IEC 61851-22	
Relative humidity	<= 95 %	

Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 1306 - Schneider Electric declaration of conformity
REACh	Reference contains SVHC above the threshold - 🗗 go to CaP for more details
Product environmental profile	Available
Product end of life instructions	Available 🔁 Download End Of Life Manual

